

# Ceramic Components for Microturbines at Kyocera

Prepared by

Dave Carruthers, Dave Carruthers & Associates, Vancouver, WA

David Bath, Kyocera Industrial Ceramics Corp. Vancouver, WA


Sazo Tsuruzono, Kyocera Corporation

Presented at the ASME Turbo Expo – Power for Land, Sea, & Air Atlanta, GA

June 16-19, 2003




#### SN281/ 282 CGT 302 Parts






# Forming Processes for GT Components, Japan






#### Organization of HGT Project






### 8000 kW HGT Project






#### **Ceramic Components for HGT**







#### Material for Microturbine Rotor (SN237)







### Hybrid Molding for Ingersol Rand Microturbine Rotor

#### Caracteristics of Forming Processes

	Slip casting	Injection molding	Hybrid molding
Mold	Plaster Mold	Metal Mold	Metal Mold
Pressure	Low	High	low
Binder Amount	Small	Large	Small
Green Density	High	Low	High






Turbocharger rotor




#### Microturbine Rotor Reliability





#### **Microturbine Rotor Life Predicted**





#### **Kyocera Industrial Ceramics**


Vancouver, WA

- Automotive Engine Components
- Aerospace Pump Components
- Aerospace Engine Seals
- Gas Turbine Components
- Aluminum Foundry Products
- Semiconductor Processing Equipment Components
- Papermaking Machine Wear Products
- Broad Range of Heat, Wear and Corrosion Resistant Parts





# **Kyocera, Vancouver Developing Bisque Processing**








# Bisque Processing Applied to Variety of Shapes



As fired tolerances +/- .75% per unit dimension As-fired surface finish to 50  $\mu$ -inch Ra Cost ~ 85% of Hybrid Molding for 300/year production



# Bisque Processing Compresses Cycle Time





# Bisque Processing Suitable for Complex Shapes





#### **Brittle Material Toll Services**

- Forming
- Machining/Grinding
- Non Oxide Materials Sintering/HIP
- Laboratory Analysis